

**PRODUCT INFORMATION**

# 13" Outdoor E-paper Display

IK09 and IP67 rated outdoor e-paper displays are supplied in a ruggedized enclosure with toughened front glass, designed to be installed within the customer's own structures or to any fixed surface. With wireless, battery and solar capabilities as standard, all models come with optional illumination, interactive functions and text-to-speech modules


**GENERAL**

Dimension (L x H x W)	275 x 383 x 46 mm
Weight	5.7 kg (12.56 lb)
Mounting type	Back VESA 100 M6 thread / side M6 screw
Colour	RAL 9006 Custom colours also available

**DISPLAY**

Display resolution	1200 x 1600 pixels
Active display area	203 x 270 mm
Pigment	Greyscale (16 levels of grey)
Display type	Reflective
Illumination	Embedded LED front illumination, adjustable
Ambient light sensor	Optional

**ENVIRONMENT**

Operating temperature	Greyscale: -20°C to +70°C (-4°F to +158°F)
Protection	IK09 and IP67

**CONNECTIVITY**

Communication	Mobile network / WiFi / Ethernet
Mobile network	3G or optional 4G/LTE
Mobile network antenna	Internal (external antenna optional)
WiFi (optional)	Dual band (2.4/5 GHz) 802.11 ac/b/g/n
WiFi antenna (optional)	External
Ethernet (optional)	10/100/1000 Mbps

**ELECTRICAL**

Power supply	12 V DC (from AC mains via power supply) or 12 V DC solar panel
Power consumption (1 min data update)	50 mA (without illumination) 60 mA (illuminated)
Power consumption (Text-to-speech)	60 mA (without illumination) 70 mA (illuminated)
Power consumption (User interaction)	70 mA (without illumination) 80 mA (illuminated) Support for full shutdown with timer
Power supply connector	Male 5-pin circular waterproof

**CERTIFICATIONS**

Certificate of Conformity, Environmental, Electromagnetic Compatibility (EMC), Radio Equipment Directive (RED), Ingress Protection Rating (min IP67), Impact Protection Rating (min IK09).