

**SVSD17M
17" SQUARE LCD DISPLAY MONITOR**



**Advanced Reflectionless Technology
Provides Authentic Image Quality for Real Life Art Work**



FULL HD DEFINITION

FULL HD resolution 1920 x 1080 ensures vivid, high-impact images and videos in Museum, Exhibition halls, Shopping malls and Supermarkets.



HIGHLY DURABLE SCREENS

Designed for continuous use in public spaces, these displays utilise commercial grade LCD panels, LED backlights and internal components. This means they can run 24/7 for over 50,000 hours.



NARROW BEZEL

These displays feature a slim border for applications where this is important, such as placing multiple screens side-by-side.



EXCEPTIONAL BRIGHTNESS

Elevated brightness 350nits provides extraordinary colour expression and greater visibility.



ANTI-GLARE LCD PANEL

With Advanced Reflectionless Technology panel, you can rest assured that your content will not be obstructed by lighting conditions outside of your control.



NATIVE SQUARE LCD

Non-resizing/cutting LCD Panel, so no Broken glass, fragile sealing, micro-cracks, light leakage.



LCD MONITOR

Users can choose the stretched display as LCD Monitor with HDMI IN only, which allows to connect to any external media player or mini PC if required.



AUO TARTAN TECHNOLOGY

AUO's original square displays, utilize AUO unique Tartan display technology. These units offer a space saving, energy-efficient and reliable display solution.

SPECIFICATIONS

Panel

Diagonal Size 17"	Resolution 1920 x 1920	Brightness (Typ.) 350 nit	Contrast Ratio 1000:1
Viewing Angle 178 / 178 (H/V)	Colors 16.7M, 72% NTSC	Surface Treat. A.R.T (Advanced Reflectionless Technology)	AA Area (mm) 305.28 x 305.28
LED Life (hrs.) 50,000 (Min.)	Display Mode Normally Black (AHVA)		

Power

Type External	Power Supply AC 100 - 240V, 50/60Hz - DC12V	Power Consumption 45W
-------------------------	-------------------------------------------------------	---------------------------------

Mechanical

Outline Size (mm) 330.8x 324.34 x 24.5mm	Weight 10 kg	Bracket Optional
----------------------------------------------------	------------------------	----------------------------

Operation

Operation Temp. 0 - 40°C	Humidity 10% - 80%
------------------------------------	------------------------------

LCD Monitor with HDMI IN Only

USB USB x 1	HDMI IN HDMI IN x 1	Auido Out Audio Out x 1
-----------------------	-------------------------------	-----------------------------------